

Customer:	Size:	Form No.	Rev.
-----------	-------	----------	------

Product Requirements

Customer PN/Project Name:			
Drawing#			
Type			
<input type="checkbox"/> Touch Window			
<input type="checkbox"/> 4-Wire <input type="checkbox"/> 5-Wire <input type="checkbox"/> 8-Wire <input type="checkbox"/> Other _____			
Dimension Definitions:			
OD :	×	×	(mm)
VA :	×	×	(mm)
AA :	×	×	(mm)
Other Information As attached			
<input type="checkbox"/> Data sheet <input type="checkbox"/> AutoCAD Drawing			
<input type="checkbox"/> Printing Artwork <input type="checkbox"/> Mechanical Design			
<input type="checkbox"/> Pin Assignment <input type="checkbox"/> Other _____			

Material Requirements

Substrate	<input type="checkbox"/> Normal Glass
	<input type="checkbox"/> Chemically Strengthened Glass
	Thickness (mm): <input type="checkbox"/> 0.7 <input type="checkbox"/> 1.1 <input type="checkbox"/> 1.8 <input type="checkbox"/> 2.8
	<input type="checkbox"/> PC <input type="checkbox"/> PMMA <input type="checkbox"/> Other: _____
	Thickness (mm) <input type="checkbox"/> 0.8 <input type="checkbox"/> 1.0 <input type="checkbox"/> 1.2 <input type="checkbox"/> 1.5 <input type="checkbox"/> 2.0 <input type="checkbox"/> Other: _____
	<input type="checkbox"/> R&D can adjust the substrate thickness based on total thickness
Printing	<input type="checkbox"/> Normal Printing
	<input type="checkbox"/> Vacuum Metallization (VM) /NCVM Color Code Reference <input type="checkbox"/> Y <input type="checkbox"/> N
Deco Film	Surface Treatment <input type="checkbox"/> Clear <input type="checkbox"/> Anti-Glare
	Thickness: <input type="checkbox"/> 125mm <input type="checkbox"/> 188mm
ITO Film	<input type="checkbox"/> Clear <input type="checkbox"/> Anti-Glare (Haze ____)
Hardness	<input type="checkbox"/> 2H <input type="checkbox"/> 3H <input type="checkbox"/> Other _____

Optical Characteristic	Newton Ring: <input type="checkbox"/> Not allowed <input type="checkbox"/> Limited Sample: Per approval sheet
	Sparkling: <input type="checkbox"/> Not Acceptable <input type="checkbox"/> Slightly OK <input type="checkbox"/> Do not concern
	Transmission rate: <input type="checkbox"/> 76% <input type="checkbox"/> 78% <input type="checkbox"/> 80% <input type="checkbox"/> Other _____
	Tail
	Type: <input type="checkbox"/> FPC <input type="checkbox"/> Housing <input type="checkbox"/> Other _____ Length: _____ (mm) Pitch (mm): <input type="checkbox"/> 0.5 <input type="checkbox"/> 1.0 <input type="checkbox"/> 2.54 <input type="checkbox"/> Other _____

Durability Requirements

Linearity Testing Force	Max. <input type="checkbox"/> 150g (SR Default) <input type="checkbox"/> 100g (Std. Res. Default) <input type="checkbox"/> Others _____
Linearity	Max. <input type="checkbox"/> 1.5% (Default) <input type="checkbox"/> 2.0% <input type="checkbox"/> 3.0%
Writing Life	Min. <input type="checkbox"/> 100K <input type="checkbox"/> 300K <input type="checkbox"/> Other _____ (Characters)
Hitting Life	Min. <input type="checkbox"/> 1Million <input type="checkbox"/> 10Million <input type="checkbox"/> Other _____ (Hits)
Actuation Force	Max : _____

Environment Testing

Operation Temp.(°C)	<input type="checkbox"/> -10C - +60C (Standard Default) <input type="checkbox"/> Other _____
Operation RH%	<input type="checkbox"/> 20-90% RH (Default) <input type="checkbox"/> Other _____
Storage Temp.(°C)	<input type="checkbox"/> -20 - +70°C (Default) <input type="checkbox"/> Other _____
Storage RH%	<input type="checkbox"/> 20-90% RH <input type="checkbox"/> Other _____

Customer:	Size:	Form No.	Rev.
-----------	-------	----------	------

Reliability

High Temp.	<input type="checkbox"/> 60°C, 90%RH, 240hr (Default)
High Hum%	<input type="checkbox"/> Other _____
Thermal Shock	<input type="checkbox"/> -20 - 80°C×10 (1hr, 5min, 1hr)
Shock	<input type="checkbox"/> Other _____
High Temp. Storage	<input type="checkbox"/> 80°C, 240hr (Default)
Storage	<input type="checkbox"/> Other _____
Low Temp. Storage	<input type="checkbox"/> -20°C, 240hr (Default)
Storage	<input type="checkbox"/> Other _____

Assembly Characteristics

How the TS is assembled with bezel?	<input type="checkbox"/> Adhesive on Film
	<input type="checkbox"/> Adhesive on Glass
	<input type="checkbox"/> No adhesive
	<input type="checkbox"/> Other _____
Water-proof Methods	<input type="checkbox"/> Silicon glue
	<input type="checkbox"/> Rubber press
	<input type="checkbox"/> Other _____

Inspection Criteria

OQC Report	<input type="checkbox"/> No need <input type="checkbox"/> Needed
	<input type="checkbox"/> Other _____
CPK	<input type="checkbox"/> No need <input type="checkbox"/> Needed <input type="checkbox"/> Other _____
Cosmetic Inspection	<input type="checkbox"/> Per Customer's requirements
	<input type="checkbox"/> Per PanJit's Standards

Other Requirements

--

Americas & Europe

Email to: us.sales@panjit.com or fax to 480-379-2819

Asia

Email to tpsales@mildex.com.tw or fax 866-7-3767